

Tender text

ESP-62AB/WS

PA A/B wall speaker,

with EN 54-24 certification for evacuation systems with A/B speaker distribution according to EN 60849.

- 100 V line technique
- 13 cm full range speaker with dual voice coil
- 2 separate transformers with power taps with 6/3/1.5 W each
- Connection via 2 ceramic screw terminals inside the cabinet
- Symmetrical design allows for horizontal and vertical mounting
- Plastic cabinet with open rear panel and protective metal front grille
- Supplied with screws and wall plugs

Specifications:

Active/passive	passive
Transmission method	100 V
Power rating (RMS)	2 x 6/3/1.5 W
Frequency range	80-19,000 Hz
Full range speaker	13 cm, dual voice coil
Number of speakers	1
Speaker size	13 cm
Sensitivity	93 dB/W/m
Max. rated SPL	101 dB
Radiation angle, horizontal	160°
Radiation angle, vertical	160°
Housing material	ABS
Colour	white, RAL 9010
Mounting device	screws
Admiss. ambient temp.	-10 °C to +55 °C
Dimensions	240 x 330 x 83 mm
Width	240 mm
Height	330 mm
Depth	83 mm
Weight	1.5 kg
Accessories	

Brand: MONACOR

Type: ESP-62AB/WS

Quantity: 1

Packing dimensions (W x H x L):

Gross weight: 1.806 kg

Net weight: 1.545 kg

Item weight (w/o accessories): 1.5 kg