

## Tender text

### ETS-8100TW/WS

#### High-quality weatherproof PA column speaker, IP66

- High-quality 2-way column speaker with excellent sound characteristics
- 100 V line technique or 8  $\Omega$  operation
- 8 x 7.7 cm (3") speaker with polypropylene cone
- 25 mm (1") centrally arranged dome tweeter
- 3 power taps: 60/30/15 W
- Power capability: 100 W in 8  $\Omega$  operation
- Connection is made via cable with high-strength cable gland (length: 2 m)
- Robust aluminium cabinet with plastic front protective grille
- Supplied with robust wall bracket for pivoting and tilting

#### Specifications:

Active/passive	passive
Transmission method	100 V
Power rating (RMS)	60/30/15 W (100 V) 100 W (8 $\Omega$ )
Impedance	8 $\Omega$
Frequency range	110-20,000 Hz
Full range speaker	8 x $\varnothing$ 77 mm
Tweeter	1
Number of speakers	9
Sensitivity	95 dB/W/m
Max. rated SPL	117 dB
Radiation angle, horizontal	70°
Radiation angle, vertical	20°
Housing material	aluminium
Colour	white
Mounting device	wall bracket
Protection class	IP66
Admiss. ambient temp.	0-40 °C
Dimensions	125 x 869 x 110 mm
Width	125 mm
Height	869 mm
Depth	110 mm
Weight	6 kg
Inputs	cable
Other features	supplied with wall bracket

Brand: MONACOR

Type: ETS-8100TW/WS

Quantity: 1

Packing dimensions (W x H x L): 0.19 x 0.2 x 1.09 m

Gross weight: 11.22 kg

Net weight: 9.46 kg

Item weight (w/o accessories): 6 kg