

Tender text

FLY-16R

16-channel wireless PA audio receiver,

with UHF PLL technology.

- For analogue wireless transmission of line audio signals in PA systems
- Frequency range: 823-832 MHz
- 16 pre-programmed channels, selectable
- Up to 8 intermodulation-free channels
- Audio transmission range: 30-17,000 Hz
- Multiple receivers FLY-16R can be operated via one transmitter FLY-16T
- Indication for channel and battery status
- 3-pole XLR jack
- Power supply via 1 x 1.5 V battery AA size (not supplied) or micro USB jack (5 V/150 mA)
- Supplied with USB cable
- Dimensions: 22 x 23 x 102 mm

There are restrictions or requirements within the EU!

Please read the notes regarding wireless systems in the section "IMPORTANT INFORMATION"!

Specifications:

General information

Description	16-channel wireless PA audio receiver
Carrier frequency range	823-832 MHz
Audio frequency range	30-17,000 Hz
Channels	16
THD	0.3%
Admiss. ambient temp.	0-40 °C
Specifications receiver	
Power supply receiver	1 x 1.5 V batt. AA size, DC 5 V/150 mA via micro USB jack
Width receiver	22 mm
Height receiver	23 mm
Depth receiver	102 mm
Weight receiver	25 g
Connections receiver	3-pole XLR plug

Brand:

Type: FLY-16R

Quantity: 1

Packing dimensions (W x H x L): 0.1 x 0.03 x 0.18 m

Gross weight: 0.068 kg

Net weight: 0.044 kg

Item weight (w/o accessories): 0.025 kg